

## BLAST CHILLER FREEZER

### CONSTRUCTION & FEATURES

- Construction of 304 stainless steel exterior/interior
- Interior with radius corners for hygiene
- Body construction of 50 mm thickness precision injection with high density polyurethane (PU) insulation. Provides excellent thermal efficiency with low global warming potential (GWP) and zero ozone depletion potential (ODP).
- Stainless handle reversible self-closing doors
- Tropicalised condensing unit. Guaranteed operation up to +43°C ambient.
- Fast cooling system technology with efficient forced air cooled system
- Ventilated refrigeration evaporator with anti-corrosion coating for hygiene and quality.
- HACCP compliant smart electronic control panel for easy operation and performance, featuring clear and precise temperature display.
- Adjustable and removable anti-tilt shelf supports and shelving system.
- Automatic defrost, defrost water is vaporized with heat recovery (No drain connection required)
- Replaceable magnetic gaskets door frame with anti-condensation system
- Fitted with LED lighting



### SPECIFICATIONS



Product Name	3-tray freezer	5-tray freezer	10-tray freezer	15-tray freezer
Model Name	TBF-3	TBF-5	TBF-10	TBF-15
Outer size (L*W*H)	710x700x560mm	800x800x1000mm	800x800x1385mm	800x800x1920mm
Inner size (L*W*H)	350x590x270mm	640x430x410mm	640x430x760mm	640x430x1110mm
Volume	3-tray/68L	5-tray/108L	10-tray/208L	15-tray/308L
Cooling method	Air-cooled	Air-cooled	Air-cooled	Air-cooled
temperature range °C	(-35)/+3	(-40)/+3	(-40)/+3	(-40)/+3
power	550W/22V/50Hz	880W//220V/50Hz	1200W/380V/50Hz	1800W/380V/50Hz
Equipment Material	SUS304	SUS304	SUS304	SUS304 stainless